

ICS 351: Today's plan

- HTML
- HTTP
- web scripting languages

HTML

- HyperText Markup Language
- an in-line way of marking (hyper)text, similar in spirit to TeX/LaTeX, and inspiring the creation of XML
- part of the markings are about style and formatting: font, size, bold/italic, bullet lists, etc.
- some markings lead you to other pages or objects, e.g.
 home page, or

objects are identified by URLs (all URLs are also URIs)
- each URL has a protocol (scheme name, e.g. http), a host identifier (DNS name or IP address), an optional port number (:80 if not specified), and the path given to the server

typical HTTP interaction

- client is given a URL, splits it into domain name (port) and path
- client resolves domain name to IP address
- client opens a connection to the IP address (port 80, or the given port), server accepts connection (TCP 3-way handshake)
- client sends HTTP request
- server sends HTTP response
- after parsing response and finding embedded images or other content, client sends new HTTP requests on same TCP connection
- server replies to each request in sequence
- client matches each response to its request, renders the page
- after a time (typically 30s), the server closes the connection

HTTP request header

- all HTTP is rendered using ASCII. This makes it easy to read, a little harder to parse
- for example, an HTTP request might look like this:

```
GET /~esb/ HTTP/1.1
```

```
Host: www2.ics.hawaii.edu
```

```
Accept: */*
```

```
Connection: close
```

HTTP response header

- a corresponding HTTP reply might look like this:

```
HTTP/1.1 200 OK
```

```
Date: Thu, 19 Nov 2009 05:18:56 GMT
```

```
Server: Apache
```

```
Last-Modified: Wed, 02 Sep 2009 03:17:30 GMT
```

```
ETag: "19abf-2095-4728fb5090680"
```

```
Accept-Ranges: bytes
```

```
Content-Length: 8341
```

```
Connection: close
```

```
Content-Type: text/html
```

```
<html>
```

```
...
```

HTTP headers

- in each case, the first line describes the main request or result:
 - o in the request, the method can be GET, HEAD, POST, or a few others,
 - o the path is specified immediately after the request,
 - o the protocol version follows the path
 - o in the reply, the version comes first, followed by the result code, both as a number and as a string
- the remaining lines of the header give more details, sometimes essential details (e.g. the content type and content length)
- each header ends with an empty line

web scripting languages

- web content described by HTML was originally static, corresponding to files on the server
- since the server is a program, it can generate content that is generated dynamically, e.g. put the user's name (or bank balance) within the web page
- however, this requires the server administrator to modify the code of the server, which is error-prone
- so instead, the server program can execute a *server-side script* to generate new content to be served
- this script can be written in any language supported by the system on which the server is running

client-side scripts

- even with a server-side script, each change in the web page requires an HTTP request and reply, and requires that the page be rendered again
- and usually requires an explicit user action such as a mouse click
- to have more interactivity, many browsers have been designed to execute *client-side scripts* that can modify the displayed page and exchange data over the internet
- client-side scripts are usually in Java or Javascript

client-side scripts and security

- while client-side scripts do much to improve the appearance of pages, there can be concerns about security and reliability
- client-side scripts let servers execute code on a client – how does the client know what the code will do? can the client trust the server?
- in an attempt to address these concerns, browsers limit what scripts are allowed to do
- not all browsers execute client-side scripts

server-side scripts and security

- bugs in a server-side script can be exploited by attackers
- server-side scripts that do not thoroughly check their input are vulnerable, e.g. to SQL injection attacks

<http://xkcd.com/327/>

- a server-side script lets the client execute code on the server
- the server controls what scripts are available, but not what the clients will do with the scripts